

according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

1.2

Registration number (REACH)

Unique formula identifier (UFI)

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses.

1.3 Details of the supplier of the safety data sheet

AprintaPro GmbH Gutheil Schoder Gasse 17 1230 Wien Austria

Telephone: +43 1 997809410 e-mail: office@aprintapro.com Website: https://www.aprintapro.com

e-mail (competent person)

1.4 Emergency telephone number

Emergency information service

Heat Resistant Resin
not relevant (mixture)

QJES-Q17S-P00W-UME7

3D printing resin

office@aprintapro.com

+43 1 997809410 This number is only available during the following office hours: Mon-Fri 08:00 - 16:00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
3.10	acute toxicity (oral)	4	Acute Tox. 4	H302
3.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.4S	skin sensitisation	1	Skin Sens. 1	H317
3.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
4.1C	hazardous to the aquatic environment - chronic haz- ard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word danger

- Pictograms

GHS05, GHS07, GHS08, GHS09





according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

- Hazard statements H302	Harmful if swallowed.	
H317	May cause an allergic skin rea	ction.
H318	Causes serious eye damage.	
H373	May cause damage to organs	through prolonged or repeated exposure.
H411	Toxic to aquatic life with long	lasting effects.
- Precautionary statemen	ts	
P101	If medical advice is needed, ha	ave product container or label at hand.
P102	Keep out of reach of children.	
P103	Read carefully and follow all ir	nstructions.
P260	Do not breathe spray.	
P280	Wear protective gloves/eye pr	otection.
P305+P351+P338	IF IN EYES: Rinse cautiously w to do. Continue rinsing.	ith water for several minutes. Remove contact lenses, if present and easy
P310	Immediately call a POISON CE	NTER/doctor.
P501	Dispose of contents/containe	r to hazardous or special waste collection point.
Tactile warning of dange		yes
- Hazardous ingredients f	or labelling	(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate, 4-(1-oxo-2-propenyl)-morpholine, phenyl bis(2,4,6-tri- methylbenzoyl)-phosphine oxide, 2-hydroxyethyl methacrylate

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\ge 0,1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Ide	ntifier	Wt%	Classification acc. to GHS
(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)- triyl)tri-2,1-ethanediyl triacrylate	CAS No	40220-08-4	25-<50	Eye Dam. 1 / H318 Skin Sens. 1 / H317 Aquatic Chronic 2 / H411
4-(1-oxo-2-propenyl)-morpholine	CAS No	5117-12-4	25-<50	Acute Tox. 4 / H302 Eye Dam. 1 / H318 Skin Sens. 1 / H317 STOT RE 2 / H373
phenyl bis(2,4,6-trimethylbenzoyl)-phos- phine oxide	CAS No	162881-26-7	2-<5	Skin Sens. 1A / H317 Aquatic Acute 1 / H400 Aquatic Chronic 4 / H413
2-hydroxyethyl methacrylate	CAS No	868-77-9	2-<5	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Skin Sens. 1 / H317

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
4-(1-oxo-2-propenyl)-morpholine	-	-	588 ^{mg} / _{kg}	oral
phenyl bis(2,4,6-trimethylben- zoyl)-phosphine oxide	-	M-factor (acute) = 10	-	

Remarks

For full text of abbreviations: see SECTION 16

Date of compilation: 2024-10-08



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed none

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits) this information is not available

	Relevant DNELs of components							
CAS No	Endpoint	Threshold level	Protection goal, route of exposure	5				
40220-08-4	DNEL	1,65 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects			
40220-08-4	DNEL	2,3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects			
5117-12-4	DNEL	132,2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects			
5117-12-4	DNEL	132,2 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects			
5117-12-4	DNEL	300 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects			
5117-12-4	DNEL	300 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects			
868-77-9	DNEL	4,9 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects			
868-77-9	DNEL	1,3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects			

	Relevant PNECs of components							
CAS No	Endpoint	Threshold level	Organism	Environmental compart- ment	Exposure time			
40220-08-4	PNEC	9,43 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)			
40220-08-4	PNEC	0,943 ^{µg} / _l	aquatic organisms	marine water	short-term (single instance)			
40220-08-4	PNEC	10 ^{mg} /l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)			
40220-08-4	PNEC	0,62 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)			
40220-08-4	PNEC	0,062 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)			

Date of compilation: 2024-10-08



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

	Relevant PNECs of components						
CAS No	Endpoint	Threshold level	Organism	Environmental compart- ment	Exposure time		
40220-08-4	PNEC	0,118 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)		
5117-12-4	PNEC	0,012 ^{mg} /I	aquatic organisms	freshwater	short-term (single instance)		
5117-12-4	PNEC	0,009 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)		
5117-12-4	PNEC	0,001 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)		
868-77-9	PNEC	0,482 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)		
868-77-9	PNEC	0,482 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)		
868-77-9	PNEC	10 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)		
868-77-9	PNEC	3,79 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)		
868-77-9	PNEC	3,79 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)		
868-77-9	PNEC	0,476 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)		

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Type of material

NBR: acrylonitrile-butadiene rubber

- Material thickness
- ≥0,6mm

- Breakthrough times of the glove material

>480 minutes (permeation: level 6)

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Filtering half mask (EN 149). P1 (filters at least 80 % of airborne particles, colour code: White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	black
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	>168 °C at 101,3 kPa
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

	Flash point	not determined
	Auto-ignition temperature	375 °C (auto-ignition temperature (liquids and gases))
	Decomposition temperature	not relevant
	PH (value)	6–8 (in aqueous solution: 100 ^{mg} / _{cm³} , 25 °C)
	Kinematic viscosity	not determined
	Solubility(ies)	not determined
	Partition coefficient	
	Partition coefficient n-octanol/water (log value)	this information is not available
	Vapour pressure	0,08 hPa at 20 °C
	Density and/or relative density	
	Density	1,1 ^g / _{cm³} at 25 °C
	Relative vapour density	information on this property is not available
	Particle characteristics	not relevant (liquid)
9.2	Other information	
	Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
	Other safety characteristics	
	Temperature class (EU, acc. to ATEX)	T2 (maximum permissible surface temperature on the equipment: 300°C)

SECTION 10: Stability and reactivity

10.1 Reactivity Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

- 10.2 Chemical stability See below "Conditions to avoid".
- 10.3 Possibility of hazardous reactions No known hazardous reactions.
- 10.4 Conditions to avoid UV-radiation/sunlight.
- 10.5 Incompatible materials Oxidisers
- 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4: May be harmful in contact with skin.



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

- Acute toxicity estimate (ATE) Oral 1.544 ^{mg}/_{kg}

Acute toxicity estimate (ATE) of components						
Name of substance CAS No Exposure route ATE						
4-(1-oxo-2-propenyl)-morpholine 5117-12-4 oral 588 ^{mg} / _{kg}						

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (chronic) of components						
CAS No	Endpoint	Value	Species	Exposure time		
162881-26-7	EC50	>100 ^{mg} /I	microorganisms	3 h		
868-77-9	EC50	90,1 ^{mg} / _l	aquatic invertebrates	21 d		
868-77-9	LC50	>100 ^{mg} /l	aquatic invertebrates	21 d		

12.2 Persistence and degradability

	Degradability of components				
CAS No	Process	Degradation rate	Time	Method	Source
40220-08-4	oxygen depletion	19,7 %	28 d		ECHA
162881-26-7	carbon dioxide genera- tion	1 %	29 d		ECHA

12.3 Bioaccumulative potential

Data are not available.



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

	Bioacc	umulative potential of components	
CAS No	BCF	Log KOW	BOD5/COD
40220-08-4		1,09 (pH value: 6,8, 25 °C)	
5117-12-4		-0,46 (21 °C)	
162881-26-7	<5	5,8 (pH value: 8,3, 22 °C)	
868-77-9		0,42 (25 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of $\ge 0,1\%$.

12.6 Endocrine disrupting properties Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

14.1		
	ADR/RID/ADN	UN 3082
	IMDG-Code	UN 3082
	ICAO-TI	UN 3082
14.2	UN proper shipping name	
	ADR/RID/ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.
	Technical name (hazardous ingredients)	(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide
14.3	Transport hazard class(es)	
	ADR/RID/ADN	9
	IMDG-Code	9
	ICAO-TI	9
14.4	Packing group	
	ADR/RID/ADN	III
	IMDG-Code	III



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Versio	n number: SDS 1.0	Date of compilation: 2024-10-08			
	ICAO-TI	III			
14.5	Environmental hazards	hazardous to the aquatic environment			
	Environmentally hazardous substance (aquatic environment)	(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide			
14.6	Special precautions for user Provisions for dangerous goods (ADR) should be complied with	nin the premises.			
14.7	Maritime transport in bulk according to IMO instruments The cargo is not intended to be carried in bulk.				
14.8	Information for each of the UN Model Regulations				
	Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information				
	Classification code	M6			
	Danger label(s)	9, fish and tree			
	Environmental hazards	yes (hazardous to the aquatic environment)			
	Special provisions (SP)	274, 335, 375, 601			
	Excepted quantities (EQ)	E1			
	Limited quantities (LQ)	5 L			
	Transport category (TC)	3			
	Tunnel restriction code (TRC)	-			
	Hazard identification No	90			
	International Maritime Dangerous Goods Code (IMDG) - Additional information				
	Marine pollutant	yes (hazardous to the aquatic environment) ((2,4,6-trioxo-1,3,5- triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate)			
	Danger label(s)	9, fish and tree			
	Special provisions (SP)	274, 335, 969			
	Excepted quantities (EQ)	E1			
	Limited quantities (LQ)	5 L			
	EmS	F-A, S-F			
	Stowage category	A			
	International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information				
	Environmental hazards	yes (hazardous to the aquatic environment)			
	Danger label(s)	9, fish and tree			
	Special provisions (SP)	A97, A158, A197, A215			
	Excepted quantities (EQ)	E1			
	Limited quantities (LQ)	30 kg			



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)			
Name of substance	Name acc. to inventory	CAS No	No
Heat Resistant Resin	this product meets the criteria for classification in accord- ance with Regulation No 1272/2008/EC		3
4-(1-oxo-2-propenyl)-morpholine	substances in tattoo inks and permanent make-up		75
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	substances in tattoo inks and permanent make-up		75
2-hydroxyethyl methacrylate	substances in tattoo inks and permanent make-up		75

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Seveso Directive

	2012/18/EU (S	eveso III)	
No	Dangerous substance/hazard categories Qualifying quantity (tonnes) for the application of lower and upper-tier requirements Notes		Notes
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200 500	57)

Notation

57) hazardous to the Aquatic Environment in category Chronic 2

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) none of the ingredients are listed

Water Framework Directive (WFD)

	List of pollutants (WFD)	
Name of substance CAS No Listed in Remarks			
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide		a)	

Legend

a) Indicative list of the main pollutants

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

Country	Inventory	Status
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
МХ	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
VN	NCI	not all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Car- riage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

Abbr.	Descriptions of used abbreviations
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in re- sponse (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a spe- cified time interval
log KOW	n-Octanol/water
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
SVHC	Substance of Very High Concern
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.



according to Regulation (EC) No. 1907/2006 (REACH)

Heat Resistant Resin

Version number: SDS 1.0

Date of compilation: 2024-10-08

Code	Text
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.